HOBART CL-VL Installation Guidelines



- A RETURN & SUPPLY AIR VENTS placed a minimum of 24" from heat pump fan enclosure (to leading edge of vent)
- B ADJACENT WALL TO EDGE OF MACHINE requires a minimum of 43" clearance to accommodate 30" table (incl. backsplash & roll) + 13" vent hood (See reverse for exploded view)
- C All ventless models come standard with 13" wide exterior vent hoods on both load and unload of dishmachine.

D ROOM CONSIDERATIONS

Dishroom Ceiling Height shall have a min. height of 96" (8') H Delivery Path (Doorways/Elevators) shall have a min. clearance of 31.5" W x 74.5" H

MACHINE TO TABLE CONNECTION DIMENSIONS

For CL44-VL models table i.d. is 43.5" For CL66-VL models table i.d is 65.5"

Shipping Dimensions & Weights

Machine & heat pump ship separately

CL44-VL



▼ Uncrated

▼ Crated

31.5" width

38" width

74.5" height (to top of Rinse Gauge)

78" height

69.5" length / *56.5" ('load vent hood removed)

74" length

Shipping Weight 729 lbs.

CL66-VL



▼ Uncrated

▼ Crated

31.5" width

38" width

74.5" height (to top of Rinse Gauge)

78" height

91.5" length / *78.5" (*load vent hood removed)

96" length

Shipping Weight 1,044 lbs.

+ Heat Pump Assembly



▼ Uncrated

▼ Crated

31" width

35" width

17" height

36" height

36" length

44" length

Shipping Weight 253 lbs.

Please refer to Spec Sheets F48941 (CL66-VL) & F48940 (CL44-VL) for all other specifications.

Latent & Sensible Heat



Latent 6,100 BTU/hr



Sensible 3,100 BTU/hr

Decibel Rating




Decibel Rating: 74 dBu

Refrigerant



Refrigerant Type: R450A Volume: 2.9 kg / 6.4 lbs

Dishmachine Placement





Adjacent Wall to Machine Load Side Table Connection

requires a minimum of 43" clearance to accommodate 30" table (including backsplash & roll) + 13" vent hood.



Let's Talk

We're ready to help you optimize your dishroom operations. Call 888-378-1338 and talk to one of our experts today.



Hobart 701 S. Ridge Ave. Troy, Ohio 45373 www.hobartcorp.com





F48951 (03-24) ©2024 Hobart