

AIR CURTAIN REFRIGERATOR MODELS



STAY IN CONTROL WITH THE VERSATILE TRAULSEN AIR CURTAIN.

Traulsen's Air Curtain Refrigerator models are efficient, mobile, and built to last. The unit is designed to streamline the traditional tray make up process, and can also facilitate service in remote dining spaces.. The unit will maintain an interior temperature of 40°F (4.4°C) or less for a minimum of 60 minutes, and up to a maximum of 120 minutes while the door is open. Keep food safe longer with the reliability of Traulsen's Air Curtain.



MOBILITY

- Heavy duty casters with stress pads
- Two (2) casters swivel with brake
- Work-flow door handle & flush hand grips
- Rear-mounted tubular handle
- · Bottom-mounted system for stability
- Full-perimeter bumper with black rubber insert



EASE OF CONTROL

- Dual stage thermostat allows users to preset temperatures prior to high-volume periods
- Settings for self defrosting, manual defrosting, and override feature



BUILT TO LAST

- Dense and environmentally friendly Polyiso Insulation
- Durable, stainless steel construction extends equipment life & minimizes service costs



EASE OF USE

- Ten pairs of tray slides for 18" x 26" pans
- "Hold open" latch to allow for easy loading and unloading
- · Push-in style magnetic door gaskets







AIR CURTAIN REFRIGERATOR MODELS



- Full Height Solid Door Hinged Right
- Voltage 120/60/1

- Full Height Solid Door Hinged Left
- Voltage 120/60/1

- Half Height Solid Door Hinged Right
- Export Voltage 220/60/1


or more information on these products visit www.traulsen.com or call 800-333-7447



SPECIAL FEATURES:

- Multi-Fan 3-D Air Screen System
 Maintains Temperature For 60 Minutes Or
 More With The Door Open
- Accommodates Standard Full, Half, Or Third-Size Pans Without Adapter Bars
- Exclusive Two-Stage/Top Mounted Electronic Temperature Control With Digital Thermometer Display
- Smart Defrost™ Automatic Defrost With Manual Override Feature





- Digital Thermometer Display
- Energy Efficient ECM Evaporator Motors
- Energy Efficient Condenser Assembly
- Full Perimeter Bumper With Black Rubber Insert
- Full & Half Length Stainless Steel Door(s) With "Hold Open" Device
- Work Flow Door Handle & Flush Hand Grips

- Set of Four (4) 6" (15 cm) High Heavy Duty Casters With Stress Pads - Two (2) Swivel With Brake
- One Piece Louver Assembly
- Push-In Style Magnetic Door Gaskets
- · Polyiso Insulation
- Ten Pairs Of Tray Slides For 18" x 26" (46 x 66 cm)Pans
- Automatic Non-Electric Condensate Evaporator

HIGHLIGHTS:



FULL PERIMETER BUMPER

For protection when re-locating the unit

REAR MOUNTED TUBULAR HANDLE

To aid in moving the unit around safely

STAINLESS STEEL HINGES

12 gauge stainless steel .320 diameter door pins

DIGITAL THERMOMETER DISPLAY

Easily read and control the features and settings