




Why	Long reliable service life	
Time required	5 minutes to prepare	15 minutes to complete
Time of day	At closing	For 24-hour restaurants: Slowest time of day

Hazard icons	 Chemicals	 Compressed Gas/Air/Liquid	 Electricity	 Hot Liquids/Steam	 Hot Oil
	 Hot Surfaces	 Manual Handling	 Moving Parts	 Moving Vehicles	
	 Sharp Objects/Surfaces	 Slippery Floors	 Syringes & Body Fluids		

Tools and supplies



Gloves & Brush, Cloth or Vacuum. A Philips Head Screwdriver is also required to perform task.

Procedure

**1 Step**  
Disconnect electrical power supply before cleaning any parts of the unit.



**4 Step**  
This will allow full access to the front facing condenser.



**2 Step**  
Remove the two screws located on both sides at the bottom of the louver.



**5 Step**  
Brush or wipe any dirt lint or dust from the finned condenser coil, the compressor and other cooling system parts. Care should be taken not to bend any of the condenser fins, as this will reduce performance and compressor life.



continued ▶

**3 Step**  
Once the screws are removed, the panel can be pivoted (lifted) upwards.



## Clean Condenser Coil (continued)

### 6 Step

Lower louver assembly back to original position and replace screws to hold it in place. When cleaning is completed plug cabinet back into proper outlet.



Moving Parts



Electricity