




Project \_\_\_\_\_  
AIA # \_\_\_\_\_ SIS # \_\_\_\_\_  
Item # \_\_\_\_\_ Quantity \_\_\_\_\_ C.S.I. Section 114000



## PW20

### Pot, Pan & Utensil Washer



### SPECIFIER STATEMENT

Specified dishwasher will be Hobart PW20 Pot/Pan/Utensil Washer, front loading with split door design, (20) pan capacity, over/under rotating arms, 2/4/6 minute adjustable timer, up to (20) racks/hour, includes: (2) flat grids, (2) tray racks & (1) flat bottom rack, pre-rinse spray hose, sanitizing with Sense-A-Temp™ 70° booster rise, vent fan control, drain pump, stainless steel construction, 208-240v/60/3-ph & 480v/60/3-ph, NSF, BISC, ENERGY STAR®.

**1 year parts and labor warranty.**

### STANDARD FEATURES

- + Timed wash cycles; racks per hour: 20 (2 minute wash), 12 (4 minute wash), 8 (6 minute wash)
- + 2.35 gallons of water per cycle
- + Hot water sanitation machines
- + Sense-A-Temp™ booster heater capable of 70° rise
- + Front loading, split-door configuration
- + Chamber accepts 20 full-sized sheet pans, or 140 quart mixing bowl
- + Advanced service diagnostics
- + 16 gauge stainless steel deep drawn tank
- + Microcomputer controls with advanced digital cycle/temperature display
- + Two revolving upper and lower anti-clogging wash arms and rinse arms
- + Removable stainless steel scrap screens and scrap basket
- + Corrosion resistant pump
- + Automatic pumped drain
- + Pumped rinse
- + 33.79" door opening
- + Automatic fill
- + Delime pump standard (Advansys)
- + Electric tank heat
- + Spray hose

### OPTIONS & ACCESSORIES (Available at extra cost)

- ☐ Pressure regulator valve 3/4"
- ☐ DWT-PW drain water tempering kit
- ☐ Steam pan rack (capacity for two racks)
- ☐ Flanged feet
- ☐ Water hammer kit
- ☐ Door height lowering kit
- ☐ Pan rack
- ☐ Combination rack

PW SERIES – PW20

Approved by \_\_\_\_\_ Date \_\_\_\_\_ Approved by \_\_\_\_\_ Date \_\_\_\_\_

### LEGEND

Electrical Connections	
<b>E1</b>	Electrical connection (including electric heat) 1-1/4" conduit hole, 7-1/16" AFF.
Plumbing Connections	
<b>P1</b>	Hot water connection incoming: 110°F water minimum. 3/4" female garden hose fitting on 6' long hose supplied with machine. 7-3/4" AFF.
<b>P2</b>	Drain connection: 7/8" barb fitting, 27-1/2" AFF. 6' long 7/8" hose supplied with machine.
<b>NOTE:</b> Cold water connection at P2 (as needed when optional drain water tempering kit is included: 55-80°F recommended water, 1/2" MPT, 26-15/16" AFF.	

**WARNING:** Plumbing and electrical connections should be made by qualified personnel who will observe all the applicable plumbing, sanitary, safety codes and National Electrical Code.

**Plumbing Notes:** Required flowing water pressure to the dishmachine is 15-65 PSIG. If pressures higher than 65 PSIG are present, a pressure regulating valve must be installed in the water line to the dishmachine (by others). Recommended water hardness to be 3 grains or less for best results. Pressure gauge not required on pumped rinse machines.

**Miscellaneous Notes:** Backflow prevention provided by NSF-approved air gap device. Single point electrical connection machines.

Electrical Specifications			
Voltage	Rated Amps	Minimum Supply Circuit Ampacity	Maximum Protective Device
208/240/60/3	58.6/64.0	70/80	80
480/60/3	35	45	45

All dimensions taken from floor line may increase 1-1/2" depending on leg adjustment.

### SPECIFICATIONS

#### Capacities

Wash Time Settings (minutes) ..... 2, 4, 6  
Racks per Hour ..... 20 (2 min. wash), 12 (4 min. wash), 8 (6 min. wash)  
Tank Capacity – Gallons ..... 34

#### Motor Horsepower

Wash ..... 4.0  
Rinse ..... 0.33

#### Water Consumption

U.S. Gallons per Cycle ..... 2.35  
U.S. Gallons per Hour (maximum use) ..... 47.0  
Peak Drain Flow – U.S. Gallons ..... 26.0

#### Temperatures °F

Wash ..... 150  
Rinse ..... 180  
Incoming Water Temperature (minimum recommended) ..... 110

#### Heating

Tank Heat, electric (kW) ..... 16.4  
Electric Booster (kW) ..... 16.4

#### Standard 20" x 20" (508 x 508) Rack Complement

Trat Rack (10 pan each) ..... 2  
Flat Grid ..... 2  
Flat Bottom ..... 1

#### Shipping Weight (approximate)

..... 705 lbs.

#### Crated Dimensions

..... 80"H x 64"W x 40"D

