



Project _____
 AIA # _____ SIS # _____
 Item # _____ Quantity _____ C.S.I. Section 114000

VBP SERIES

Holding & Transport Cabinets



Model VBP18ES
with optional bumper

SELL SHEET



SPECIFIER STATEMENT

Vulcan Model No. VBP heated holding and transport cabinets. Blower motor for gentle and even temperature distribution. Complete with 5" heavy duty casters (2 swivel with brakes and 2 rigid) (VBP5ES has 3" casters). Electronic control with digital display for holding at temperatures up to 200°F. Adjustable racking will hold 18" x 26" or 12" x 20" pans or a combination of both on 1½" centers. Lip-load racking will hold 18" x 26" pans on 1½" centers. Shelving will hold a variety of pan sizes. Complete with universal tray slides adjustable on 1½" centers. Cabinet interior and exterior are both constructed out of 20 gauge stainless steel. Recessed side-mounted handles, magnetic action door latch, and full insulation; 1½" in side walls and 2" in top. Integrated steel frame for maximum strength. Field reversible doors. Complete with rear mounted cord and plug: NEMA 5-15 for 120 volts and NEMA 6-15 for 208-240 volts. One year limited parts and labor warranty. After the first year, 10-year parts warranty on the heating elements.

UL Listed. UL Listed to Canadian safety standards. Classified by UL to NSF Standard #4.

MODELS

Units with adjustable racking:

- VBP5ES** (see reverse for capacities)
- VBP7ES** (see reverse for capacities)
- VBP13ES** (see reverse for capacities)
- VBP15ES** (see reverse for capacities)
- VBP18ES** (see reverse for capacities)

Units with lip-load racking:

- VBP7LL** (Fifteen 18" x 26" x 1" sheet pans)
- VBP15LL** (Thirty 18" x 26" x 1" sheet pans)

Units with shelves:

- VBP7SL** (Three Shelves)
- VBP15SL** (Six Shelves)

STANDARD FEATURES

- Holding Capacity:
 - 18" x 26" sheet pans
 - 12" x 20" pans, or a combination of both on 1½" centers
 - Other pan sizes on shelves
- Electronic control with digital display for holding at temperatures up to 200°F
- Blower motor for gentle and even temperature distribution
- Dutch doors (size 15 and 18 models)
- 5" heavy duty casters (2 swivel with brakes and 2 rigid) (3" on size 5 models)
- Recessed side mounted handles
- Universal tray slides adjustable on 1½" centers; VBP15ES & VBP13ES ship with 10 pairs of tray slides; VBP7ES & VBP5ES ships with 5 pairs, VBP18ES ships with 15 pairs
- Interior and the exterior are both constructed out of 20 gauge stainless steel
- Fully insulated with 1½" in side walls and 2" in top
- Integrated steel frame for maximum strength
- Magnetic action door latch
- Field reversible doors
- Rear mounted cord
- Complete with cord and plug: NEMA 5-15 for 120 volts and NEMA 6-15 for 208-240 volts
- One-year limited parts and labor warranty; after the first year, 10-year parts warranty on the heating elements


OPTIONS

- 208/240 volt
- Humidity pan
- Full perimeter bumper
- Glass Dutch doors (sizes 7 and 15 only. Non Energy Star®)
- Wire shelves to sit on tray slides
- Additional tray slides
- Mechanical control


VBP SERIES – Holding & Transport Cabinets

Approved by _____ Date _____ Approved by _____ Date _____


Drawings shown with optional bumper




All Models Top View




VBP5 Front & Side Views



VBP7 Front & Side Views



VBP13 Front & Side Views



VBP15 & VBP18 Front & Side Views

INSTALLATION MANUAL

CAD and/or Revit Files Available

This appliance is manufactured for commercial use only and is not intended for home use.

Model	Dimensions	Capacity		Electrical			Shipping Weights	
	Exterior	12" x 20" x 2½" Pans	18" x 26" Sheet Pans	Volts	Watts	Amps	Lbs.	KG
VBP5ES	27¼" W x 33¾" D x 30½" H	10	5	120	1,500	12.5	173	79
VBP7ES	27¼" W x 33¾" D x 40¼" H	14	7	120	1,500	12.5	198	90
VBP7LL	27¼" W x 33¾" D x 40¼" H	N/A	15	120	1,500	12.5	198	90
VBP7SL	27¼" W x 33¾" D x 40¼" H	14	7	120	1,500	12.5	198	90
VBP13ES	27¼" W x 33¾" D x 59¾" H	26	13	120	1,500	12.5	270	123
VBP15ES	27¼" W x 33¾" D x 65½" H	30	15	120	1,500	12.5	297	135
VBP15LL	27¼" W x 33¾" D x 65½" H	N/A	30	120	1,500	12.5	297	135
VBP15SL	27¼" W x 33¾" D x 65¼" H	30	15	120	1,500	12.5	297	135
VBP18ES	27¼" W x 33¾" D x 69½" H	36	18	120	1,500	12.5	337	153

Optional bumper adds ¾" to the width and 1½" to the depth.

Base (ES) models include fully adjustable tray slides. SL models include adjustable shelves. VBP7SL includes 3 shelves; VBP15SL includes 6 shelves. LL models include fixed lipload racking. Optional glass doors nullify ENERGY STAR® certification.

As continued product improvement is a policy of Vulcan, specifications are subject to change without notice.